



SCHEDA TECNICA

VETRINA TEMPERATURA NEGATIVA MARIN 340 / 470 RS/RV TB

340	470
RS TB	RV TB

External Dimension(LxPxH) Dimensioni Esterne	520x 740x1935 mm	670x740x1935 mm
Capacity (Gross/Net) Capacità (Lorda/Netta)	353 / 296 Lt	485 / 315 Lt
Refrigeration Refrigerazione	Static Statica	Ventilated Ventilata
Weight(Net) Peso (Netto)	108 Kg	128 Kg
Refrigerant Refrigerante	R290	
Climate Class Classe Climatica	7	7
Operating Condition Condizioni Ambientali	35° C / 75 %RH	
Energy Class Classe Energetica	***	D
Product Temperature Temperature Prodotto	-18	-18 / -16 °C
Compressor (Q.ty - Type) Compressore (Q.tà - Tipologia)	1 Hermetic 1 Ermetico	
Defrost Sbrinamento	Manual Manuale	Hot gas Gas caldo
Power Supplay Alimentazione	230 V / 1 ph / 50 Hz	
Electrical input (nominal) Assorbimento Elettrico (regime)	700 W / 4 A	750 W / 2,7 A
Electrical Input (defrost) Assorbimento Elettrico(sbrinamento)	°	1170 W / 4 A